



| | | | | | | | | | | | | | | | | | | |
|---------|-----|-----|-----|-----|-----|-----|-----|-----|----|------------------------|----|---------------------|--------|--------|--------|--------|------------------|--------------|
| ESV-300 | 300 | 380 | 280 | 200 | 360 | 275 | 570 | 360 | 40 | 13.4 | 90 | 80% | 12.5 | 16.7 | 20.9 | 25.1 | 112 | |
| | | | | | | | | | | | | 60% | 9.4 | 12.5 | 15.7 | 18.8 | | |
| ESV-250 | 250 | 326 | 233 | 150 | 313 | 275 | 520 | 310 | 35 | 7.5 | 90 | 80% | 7.0 | 9.36 | 11.7 | 14.0 | | |
| | | | | | | | | | | | | 60% | 5.3 | 7.0 | 8.8 | 10.5 | | |
| ESV-180 | 220 | 320 | 240 | 132 | 256 | 180 | 400 | 285 | 30 | 3.8 | 60 | 80% | 3.5 | 4.7 | 5.9 | 7.1 | 75 | |
| | | | | | | | | | | | | 60% | 2.7 | 3.5 | 4.4 | 5.3 | | |
| ESV-130 | 220 | 320 | 240 | 132 | 204 | 130 | 350 | 285 | 30 | 2.7 | 60 | 80% | 2.5 | 3.4 | 4.2 | 5.0 | 45 | |
| | | | | | | | | | | | | 60% | 1.9 | 2.5 | 3.1 | 3.8 | | |
| MODELO: | A | B | C | D | E | F | G | H | Ød | Vol./Vuelta [l/RPM] | le | Coef. de llenado | 30 RPM | 40 RPM | 60 RPM | 80 RPM | Potencia [HP] | Peso [Kg] |

Nos reservamos el derecho de modificar diseños, materiales y datos sin indicación previa



TECNOMILLS

Denominación:

VÁLVULA ESCLUSA